


PICTURE CODING DEVICE

Patent number: JP6078295
Publication date: 1994-03-18
Inventor: MURAKAMI ATSUMICHI; UESAWA ISAO; ITO
ATSUSHI
Applicant: MITSUBISHI ELECTRIC CORP
Classification:
- **International:** H04N7/137; G06F15/66
- **european:**
Application number: JP19920250420 19920827
Priority number(s): JP19920250420 19920827

Report a data error here

Abstract of JP6078295

PURPOSE: To improve the coding efficiency by applying variable length coding to significant/insignificant information while the information is collected every M pieces of large blocks. **CONSTITUTION:** A difference signal series 203 is obtained from an inputted signal series 202 by subtracting a preceding signal series 204 on the same position of a picture stored in a frame memory 103 from the series 202. Then a block coding device 102 identifies significance/insignificance of the difference signal series based on a threshold level 300 to apply block coding only to the difference signal coding signal 203 of a significant block. A block decoder 104 decodes a block coding signal 206 to obtain a decoded difference signal series 207 and adds it to the preceding signal series 204 to obtain a decoded signal series 208. The decoded signal series 208 is fed to the frame memory 103. On the other hand, A significance/insignificance identification signal 205 is integrated further for each of M-sets in a block processing circuit and a pattern discrimination circuit discriminates whether a consecutive number of the integrated information sets is to be coded or their combinations are to be coded.



Data supplied from the esp@cenet database - Worldwide